

SPECIFICATIONS:

The Family of EVO descenders was developed for use in vertical activities, including: Rope Access, Rescue Rope Systems, work at height and adventure activities, including: Rappelling, waterfalls descent and ravines. The EVO was tested in conformance of the standard EN 12841:2006 Type C to be used with semi static low stretch ropes with a diameter between 10,5 and 11,5mm. The EVO D01 is a Self-Locking Descender with an Anti-Panic System. This resource anti-panic gives extra protection in case of the user activate the lever accidentally. The EVO D01 is equipped with: Anti-Panic System and clip gate that facilitates the placement and the withdrawal of the rope. This model is the most complete of the line.

EVO

Ø	10.5 - 11.5 mm
EN	12841 Tipo C
EN	341 Classe A
COD:	D01

EVO



This equipment allows that the user makes tricks like:

- Control descents by rope
- Move yourself on horizontal and inclined planes Positioning on the work point without blocking or tie the equipment
- Could be used to make a charge transport system in progression, and short ascents with rope (through the addition of foot loop of one step STec S01)
- The side plate with clip, allows the user to put and remove the EVO quickly of the rope
- The braking system allows charge and people descents in controlled ways.
- The model EVO D01 is equipped with Anti-Panic System

ADDITIONAL INFORMATION

Model: D01

Color: Bronze

Anti-Panic System

Materials: Aluminum, Stainless Steel, Nylon.

Certification: EN 12841:2006 Type C

Weight: 310g



NECESSARY CAUTIONS:

- Avoid contact with chemical products that may damage to the equipment
- Do not make any repair or modification on the equipment
- Realize periodic inspections on the equipment and note on a registration sheet
- In case of any doubt about the integrity of the equipment, do not use the same.